

## PERFORMANCE VERIFICATION PROGRAMME DATA SHEET



## **ROTARY COMPRESSOR: VARIABLE SPEED / FREQUENCY DRIVE**

MODEL DATA - FOR COMPRESSED AIR									
1	Manufacturer:	CompAir							
2	Model No:	o: L07e RS Air Cooled				Date:	01.08.2024 Regulated Speed		
	Water Cooled					# of Stages:	1		
		Other	Please State:						
3	Full Load Opera	ting Pressure		7.5	bar g				
4	Drive Motor Nominal Rating			7.5	kW				
5	Drive Motor Nominal Efficiency			90.1	% (percent)				
6	Fan Motor Nominal Rating (if applicable)			n/a	kW				
7	Fan Motor Nominal Efficiency			n/a	% (percent)				
	Range		Input Power (kW)	Capacity (m3/min)	Specific Power (kW/m³/min)	Isentropic Efficiency (%)			
8	Maximum Speed 100%		9.43	1.26	7.48	65.71%	1		
	8.49 7.54			1.11	7.65	64.30%			
				0.95	7.94	61.96%			
			6.61	0.79	8.37	58.77%			
	Minimu	m Speed	4.87	0.48	10.15	48.47%	]		
9	Total Package Input Power at Zero Flow		1.3	kW					
10	Specific Power (kW/m3/min)	.00 .00 .00 .00 .00							
				0.4 0.6 Capacity (m³/min) nly a visual representation of the data /m³/min increments X-Axis Scale, 0 to	in Section 8	1 1.	2 1.4		

<sup>\*</sup>For models that are tested in the BCAS Data Sheet & Verification Programme, these items are verified by the third party administrator. Consult BCAS website for a list of participants in the third party verification programme: www.bcas.org.uk

## Notes:

- a. Measured at the discharge terminal point of the compressor in accordance with ISO1217, Annex E; m³/min is cubic metres per minute at inlet conditions.
- b. The operating pressure at which the capacity (item 8) and Electrical Consumption (Item 8) were measured for this data sheet.
- c. No Load Power in accordance with ISO1217, Annex E, if measurement of no load power equals less than 1%, manufacturer may state "not significant" or "0" on the test report.
- d. Tolerance is specified in ISO1217, Annex E, as shown in table below:
- e. The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power					
m³/min	%	%	%					
Below 0.5	+/- 7	+/- 8						
0.5 to 1.5	+/- 6	+/- 7	+/- 10					
1.5 to 15	+/- 5	+/- 6	17-10					
Above 15	+/- 4	+/- 5						