

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer:	ELGi	
2	Model No:	EN11-9.5	Date: 9/11/2025
	✓	Air Cooled	Type: Screw
	-	Water Cooled	# of SS: SS
	-	Other Please State: -	
3*	Rated Capacity at Full Load Operating Pressure ^{a,e}		1.48 m ³ /min ^{a,e}
4*	Full Load Operating Pressure ^b		9.5 bar g ^b
5	Maximum Full Flow Operating Pressure ^c		9.70 bar g ^b
6	Drive Motor Nominal Rating		11.0 kW
7	Drive Motor Nominal Efficiency		91.2% % (percent)
8	Fan Motor Nominal Rating (if applicable)		0.179 x1 kW
9	Fan Motor Nominal Efficiency		NA % (percent)
10*	Total Package Input Power at Zero Flow ^e		5.24 kW ^e
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d		13.10 kW ^d
12	Package Specific Power at Rated Capacity and Full Load Operating Pressure ^e		8.85 kW/m ³ /min ^e
13	Isentropic Efficiency		63.10 % (percent)

*For models that are tested in the BCAS Data Sheet & Verification Programme, these items are verified by the third party administrator. Consult BCAS website for a list of participants in the third party verification programme: www.bcas.org.uk

Notes:

- Measured at the discharge terminal point of the compressor in accordance with ISO1217, Annex E; m³/min is cubic metres per minute at inlet conditions.
- The operating pressure at which the capacity (item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- Maximum pressure attainable at full flow, usually the unload pressure setting for load / no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- Total package input power at other than reported operating points will vary with control strategy.
- Tolerance is specified in ISO 1217, Annex C, as shown in table below:
The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ /min	%	%	%
Below 0.5	+/- 7	+/- 8	+/- 10
0.5 to 1.5	+/- 6	+/- 7	
1.5 to 15	+/- 5	+/- 6	
Above 15	+/- 4	+/- 5	

This form was developed by the British Compressed Air Society (BCAS) for the use of its members participating in the DS&VP. BCAS has not independently verified the reported data.

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer:	ELGi	
2	Model No:	EN11-10	Date: 9/11/2025
	✓	Air Cooled	Type: Screw
	-	Water Cooled	# of SS: SS
	-	Other Please State: -	
3*	Rated Capacity at Full Load Operating Pressure ^{a,e}		1.48 m ³ /min ^{a,e}
4*	Full Load Operating Pressure ^b		10.0 bar g ^b
5	Maximum Full Flow Operating Pressure ^c		10.20 bar g ^b
6	Drive Motor Nominal Rating		11.0 kW
7	Drive Motor Nominal Efficiency		91.2% % (percent)
8	Fan Motor Nominal Rating (if applicable)		0.179 x1 kW
9	Fan Motor Nominal Efficiency		NA % (percent)
10*	Total Package Input Power at Zero Flow ^e		5.44 kW ^e
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d		13.60 kW ^d
12	Package Specific Power at Rated Capacity and Full Load Operating Pressure ^e		9.19 kW/m ³ /min ^e
13	Isentropic Efficiency		62.50 % (percent)

*For models that are tested in the BCAS Data Sheet & Verification Programme, these items are verified by the third party administrator. Consult BCAS website for a list of participants in the third party verification programme: www.bcas.org.uk

Notes:

- Measured at the discharge terminal point of the compressor in accordance with ISO1217, Annex E; m³/min is cubic metres per minute at inlet conditions.
- The operating pressure at which the capacity (item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- Maximum pressure attainable at full flow, usually the unload pressure setting for load / no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- Total package input power at other than reported operating points will vary with control strategy.
- Tolerance is specified in ISO 1217, Annex C, as shown in table below:
The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ /min	%	%	%
Below 0.5	+/- 7	+/- 8	+/- 10
0.5 to 1.5	+/- 6	+/- 7	
1.5 to 15	+/- 5	+/- 6	
Above 15	+/- 4	+/- 5	

This form was developed by the British Compressed Air Society (BCAS) for the use of its members participating in the DS&VP. BCAS has not independently verified the reported data.

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer:	ELGi	
2	Model No:	EN11-8	Date: 9/11/2025
	✓	Air Cooled	Type: Screw
	-	Water Cooled	# of SS: SS
	-	Other Please State: -	
3*	Rated Capacity at Full Load Operating Pressure ^{a,e}		1.67 m ³ /min ^{a,e}
4*	Full Load Operating Pressure ^b		8.0 bar g ^b
5	Maximum Full Flow Operating Pressure ^c		8.20 bar g ^b
6	Drive Motor Nominal Rating		11.0 kW
7	Drive Motor Nominal Efficiency		91.2% % (percent)
8	Fan Motor Nominal Rating (if applicable)		0.179 x1 kW
9	Fan Motor Nominal Efficiency		NA % (percent)
10*	Total Package Input Power at Zero Flow ^e		5.34 kW ^e
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d		13.35 kW ^d
12	Package Specific Power at Rated Capacity and Full Load Operating Pressure ^e		7.99 kW/m ³ /min ^e
13	Isentropic Efficiency		63.70 % (percent)

*For models that are tested in the BCAS Data Sheet & Verification Programme, these items are verified by the third party administrator. Consult BCAS website for a list of participants in the third party verification programme: www.bcas.org.uk

Notes:

- Measured at the discharge terminal point of the compressor in accordance with ISO1217, Annex E; m³/min is cubic metres per minute at inlet conditions.
- The operating pressure at which the capacity (item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- Maximum pressure attainable at full flow, usually the unload pressure setting for load / no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- Total package input power at other than reported operating points will vary with control strategy.
- Tolerance is specified in ISO 1217, Annex C, as shown in table below:
The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ /min	%	%	%
Below 0.5	+/- 7	+/- 8	+/- 10
0.5 to 1.5	+/- 6	+/- 7	
1.5 to 15	+/- 5	+/- 6	
Above 15	+/- 4	+/- 5	

This form was developed by the British Compressed Air Society (BCAS) for the use of its members participating in the DS&VP. BCAS has not independently verified the reported data.

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer:	ELGi	
2	Model No:	EN11-7	Date: 9/11/2025
	✓	Air Cooled	Type: Screw
	-	Water Cooled	# of SS: SS
	-	Other Please State: -	
3*	Rated Capacity at Full Load Operating Pressure ^{a,e}		1.78 m ³ /min ^{a,e}
4*	Full Load Operating Pressure ^b		7.0 bar g ^b
5	Maximum Full Flow Operating Pressure ^c		7.20 bar g ^b
6	Drive Motor Nominal Rating		11.0 kW
7	Drive Motor Nominal Efficiency		91.2% % (percent)
8	Fan Motor Nominal Rating (if applicable)		0.179 x1 kW
9	Fan Motor Nominal Efficiency		NA % (percent)
10*	Total Package Input Power at Zero Flow ^e		5.47 kW ^e
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d		13.67 kW ^d
12	Package Specific Power at Rated Capacity and Full Load Operating Pressure ^e		7.68 kW/m ³ /min ^e
13	Isentropic Efficiency		61.60 % (percent)

*For models that are tested in the BCAS Data Sheet & Verification Programme, these items are verified by the third party administrator. Consult BCAS website for a list of participants in the third party verification programme: www.bcas.org.uk

Notes:

- Measured at the discharge terminal point of the compressor in accordance with ISO1217, Annex E; m³/min is cubic metres per minute at inlet conditions.
- The operating pressure at which the capacity (item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- Maximum pressure attainable at full flow, usually the unload pressure setting for load / no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- Total package input power at other than reported operating points will vary with control strategy.
- Tolerance is specified in ISO 1217, Annex C, as shown in table below:
The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ /min	%	%	%
Below 0.5	+/- 7	+/- 8	+/- 10
0.5 to 1.5	+/- 6	+/- 7	
1.5 to 15	+/- 5	+/- 6	
Above 15	+/- 4	+/- 5	

This form was developed by the British Compressed Air Society (BCAS) for the use of its members participating in the DS&VP. BCAS has not independently verified the reported data.

MODEL DATA - FOR COMPRESSED AIR			
1	Manufacturer:	ELGi	
2	Model No:	EN11-12.5	Date: 9/11/2025
	✓	Air Cooled	Type: Screw
	-	Water Cooled	# of SS: SS
	-	Other Please State: -	
3*	Rated Capacity at Full Load Operating Pressure ^{a,e}		1.23 m ³ /min ^{a,e}
4*	Full Load Operating Pressure ^b		12.5 bar g ^b
5	Maximum Full Flow Operating Pressure ^c		12.70 bar g ^b
6	Drive Motor Nominal Rating		11.0 kW
7	Drive Motor Nominal Efficiency		91.2% % (percent)
8	Fan Motor Nominal Rating (if applicable)		0.179 x1 kW
9	Fan Motor Nominal Efficiency		NA % (percent)
10*	Total Package Input Power at Zero Flow ^e		5.33 kW ^e
11	Total Package Input Power at Rated Capacity and Full Load Operating Pressure ^d		13.31 kW ^d
12	Package Specific Power at Rated Capacity and Full Load Operating Pressure ^e		10.82 kW/m ³ /min ^e
13	Isentropic Efficiency		59.50 % (percent)

*For models that are tested in the BCAS Data Sheet & Verification Programme, these items are verified by the third party administrator. Consult BCAS website for a list of participants in the third party verification programme: www.bcas.org.uk

Notes:

- Measured at the discharge terminal point of the compressor in accordance with ISO1217, Annex E; m³/min is cubic metres per minute at inlet conditions.
- The operating pressure at which the capacity (item 3) and Electrical Consumption (Item 11) were measured for this data sheet.
- Maximum pressure attainable at full flow, usually the unload pressure setting for load / no load control or the maximum pressure attainable before capacity control begins. May require additional power.
- Total package input power at other than reported operating points will vary with control strategy.
- Tolerance is specified in ISO 1217, Annex C, as shown in table below:
The terms "power" and "energy" are synonymous for purposes of this document.

Volume Flow Rate at specified conditions	Volume Flow Rate	Specific Energy Consumption	No Load / Zero Flow Power
m ³ /min	%	%	%
Below 0.5	+/- 7	+/- 8	+/- 10
0.5 to 1.5	+/- 6	+/- 7	
1.5 to 15	+/- 5	+/- 6	
Above 15	+/- 4	+/- 5	

This form was developed by the British Compressed Air Society (BCAS) for the use of its members participating in the DS&VP. BCAS has not independently verified the reported data.